



ULTRAVIOLET FLAME DETECTOR

Omniguard® model 660

The Omniguard® model 660 UV flame detector is designed to detect unwanted fires, and output appropriate alarm information. The model 660 senses ultraviolet radiation in the appropriate wavelength for extremely fast fire detection. The model 660 will sense both hydrocarbon and non-hydrocarbon fires, a technology which has proven itself over decades of reliable service.

The model 660 is available in two versions, one for standard industrial applications where a maximum operating temperature of 85°C is the norm, and a second which is capable of operating at a maximum sustained temperature of 125°C. This version is especially well suited for turbine enclosure and high temperature industrial applications. Both versions are available with an automatic self-test function to monitor the detector's ability to sense fires and report a fault condition when impaired.



Typical applications: turbine enclosures, generator rooms, munitions facilities, battery rooms, and gas cabinets.

Key features

- Available in special high temperature version (-40°C to +125°C)
- All inclusive three-year warranty on parts and labor
- Widest field of view in the industry (120°)
- Robust, weatherproof enclosure for indoor or outdoor applications
- FM, CSA, IECEx and ATEX approved
- Improved, advanced through-the-lens diagnostic self-test
- Long range detection
- Self-contained, explosion-proof enclosure
- Economical no-test version available
- Field configurable relays and sensitivity
- State-of-the-art microprocessor control
- High intensity, localized indication of fire or fault

Specifications

Performance ratings

Responsive to hydrocarbon (gasoline, propane, methane, alcohol, etc) and non-hydrocarbon (hydrogen, silane, hydrazine, magnesium, etc) flames.

Third-party performance certified to detect saturating signal source in 15 milliseconds, 1 square foot gasoline flame at 50 feet in 1 second. Horizontal performance envelope of 120°.

Environmental ratings

Rated:

Class I, Division 1, Groups B, C & D (explosion proof)
Class II, Division 1, Groups E, F & G (dust ignition proof)
NEMA 4X weatherproof, dust-tight, watertight
CE0081 Ex II 2 G/D
Ex d IIB + H₂ T5 Gb for gas on 660-0XXXX
Ex tb IIIC T100°C Db IP6X for dust on 660-0XXXX
Ex d IIB + H₂ T4 Gb for gas on 660-1XXXX
Ex tb IIIC T135°C Db IP6X for dust on 660-1XXXX

Standard housing is copper-free aluminium conversion coated to MIL-C-5541C, Class 3 (white). Optional stainless steel housing available with passive finish per MIL-5-5002C, Type 1.

Standard operating temperature range: -40° to +85°C (-40° to +185°F).

Special high temperature version: -40° to +125°C (-40° to +257°F).

Omniguard® model 660

Specifications (continued)

Spectral response

Ultraviolet peak sensitivity of 2,2 µm.

Detector inputs

Inputs

- nominal voltage 24 VDC (ripple voltage <240mV)
- range 20 to 30 VDC

Power consumption

- standby 90 mA
- alarm 110 mA
- auto and manual test 250 mA

Detector outputs

Relay

- relays (2) fire, trouble, dry contacts, hermetically sealed
- rated 2 A at 28 VDC. User selects NO or NC
- fire relay user selects latching or non-latching

Current loop (standard version) 0 to 20 mA output

- 20 mA = fire
- 4 mA = ready
- 0 mA = 20

Programmable RS-485 serial output

Mechanical considerations

- Weight 5 lb (aluminum)
13 lb (stainless steel)
- Height x width 4.90 in x 5.50 in
- Conduit entry 3/4-14 NPTF or M20-1.5

Optional accessories

- Swivel mount No 4651027 (used with aluminum)
No 70991 (used with stainless steel)
- Portable test unit No 43808-2
- Air shield assy kit No 8001023

Ordering information

To order, please specify

Type	Omniguard® model 660
Designation	Ultraviolet flame detector
Ordering number	660 - X X X O O
Fire type	0 Industrial temperature fire detector 1 High temperature fire detector
Housing material/conduit entry	0 aluminum, 3/4-14 NPT (white) 2 stainless steel, 3/4-14 NPT 3 aluminum, M20-1.5 (white) 5 stainless steel, M20-1.5
Test feature	0 no self-test 1 auto self-test
Fire relay configuration	
Agency approvals	Factory Mutual (FM) ATEX Canadian Standards Association (CSA) California State Fire Marshall (CSFM) IECEX



Firefly AB
Phone: +46 (0)8 449 25 00
Fax: +46 (0)8 449 25 01
E-mail: omniguardsales@firefly.se
www.omniguardbyfirefly.se

Address
Textilgatan 31
120 30 Stockholm
Sweden

